


WATERPROOF V

1500 60 830/840/850 ML IP66

The WATERPROOF moisture-proof luminaire offers energy-efficient lighting solutions in three performance classes, with up to 180 lm/W, IP66, IK08 and a service life of up to 100,000 hours. Thanks to tool-free cap opening and integrated through-wiring, installation is particularly quick. Optionally with DALI and sensor - ideal for industry, warehouses or underground car parks.



TECHNICAL DATA

Item no.	1010836
IP Code	IP65
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	23 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	28
Number of luminaires at LS C16A	47
Level of inrush current	17.7 A
Duration of inrush current	224 µs
Lumen	3448 / 6230 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	120 °
Color	white
CRI	80
Service life	50000 h
Risk Group	1

Length	150 cm
Width	8.3 cm
Height	8.2 cm
Net weight	1.6 kg
Gross weight	1.82 kg