


# TRACKSPOT P 3PH. 59 930 | WB ML WH DALI SAN

**TRACKSPOT P, 3PH. 59 930 WB ML WH DALI SAN**

The TRACKSPOT P is a high-performance LED spotlight solution for 3-phase tracks and was developed for demanding retail and presentation applications. With its multi-lumen function, precise beam angles and optional DALI control, it enables maximum flexibility and high-quality, object-specific accent lighting.




## Light source

| | |
|---|---|
| 2194030 | A B |

| | |
|---|---|
| Item no. | 1011134 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Assembly | Track |
| Assembly details | Ceiling,Wall, |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~ 0/50/60Hz |
| Secondary power / voltage | 300-1050mA |
| Safety class | II |
| Wattage | 12 W |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 35°C |
| Number of luminaires at LS B16A | 27.0 |
| Number of luminaires at LS C16A | 44.0 |
| Level of inrush current | 18 A |
| Duration of inrush current | 3 µs |
| Beam angle | 47° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L70B10 |
| Service life | 50 000 h |
| Length | 17.3 cm |
| Width | 17.8 cm |
| Height | 14 cm |
| Net weight | 0.78 kg |
| Gross weight | 0.91 kg |