


DOWNLIGHT P | 84 12 HG 830 60 ML DALI WH IP54

DOWNLIGHT P, 84 12 HG 830 60 ML DALI WH IP54

The ceiling recessed luminaire DOWNLIGHT P is designed for indoor use, for example in offices, corridors, or retail spaces. It features a round shape with a product diameter of 8.6 cm and an installation depth of 5.7 cm. The luminaire is made of aluminium and offers a luminous flux ranging from 520 to 1450 lumens. The colour temperature is 3000 Kelvin (warm white), providing a pleasant, neutral lighting. Dimming is carried out via the DALI-2 protocol, allowing flexible control options. The luminaire has an IP54 rating for protection against dust and splashing water and an impact resistance of IK08, making it robust against mechanical influences. The LED lifespan is specified as 50,000 hours.



Light source

2544945	A G C

Item no.	1011289
IP Code	IP20/IP54
Impact resistance class	IK08
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150/200mA
Safety class	II
Wattage	6 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	60.0
Level of inrush current	7.9 A
Duration of inrush current	3 µs
Beam angle	60°
Color	white
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Depth	5.7
Diameter	8.6 cm
Net weight	0.35 kg
Gross weight	0.43 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	6.8 cm