


DOWNLIGHT P | 84 12 HG 830 60 ML WH IP54

DOWNLIGHT P, 84 12 HG 830 60 ML WH IP54

The ceiling recessed luminaire DOWNLIGHT P is designed for installation in ceilings and is suitable for use in indoor areas requiring protected and robust lighting. It features a round shape with a diameter of 8.6 cm and an installation depth of 5.7 cm. The luminaire is equipped with an aluminium housing and provides a light output ranging from 530 to 1470 lumens with a lifespan of 50,000 hours. The IP54 protection rating ensures protection against dust deposits and splashing water, while the IK08 impact resistance rating accounts for mechanical stress. This technical specification makes the luminaire suitable for a wide range of applications in commercial or public buildings where reliable and durable lighting is required.



Light source

2544945	A C G

Item no.	1011290
IP Code	IP20/IP54
Impact resistance class	IK08
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150/200mA
Safety class	II
Wattage	6 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	60.0
Level of inrush current	7.9 A
Duration of inrush current	3 µs
Beam angle	60°
Color	white
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Depth	5.7
Diameter	8.6 cm
Net weight	0.35 kg
Gross weight	0.43 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	6.8 cm