


DOWNLIGHT P | 84 12 WM 830 60 ML WH IP54

DOWNLIGHT P, 84 12 WM 830 60 ML WH IP54

The ceiling recessed luminaire DOWNLIGHT P is designed for installation in indoor ceilings and is particularly suitable for areas requiring protection class-rated lighting. It features a ROUND design with a product diameter of 8.6 cm and an installation depth of 5.7 cm. The housing is made of aluminium, ensuring a robust and durable construction. The luminaire offers a light output ranging from 530 to 1480 lumens and a declared lifespan of 50,000 hours. With an IP54 rating, it is protected against dust and splashing water, and it also has an impact resistance class of IK08, ensuring high durability against mechanical impacts. These features make the luminaire a reliable solution for demanding installation situations.



Light source

2544945	A C G

Item no.	1011291
IP Code	IP20/IP54
Impact resistance class	IK08
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150/200mA
Safety class	II
Wattage	6 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	60.0
Level of inrush current	7.9 A
Duration of inrush current	3 µs
Beam angle	60°
Color	white
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Depth	5.7
Diameter	8.6 cm
Net weight	0.35 kg
Gross weight	0.43 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	6.8 cm