


DOWNLIGHT P | 230 40 HG 830 60 ML DALI WH IP54

DOWNLIGHT P, 230 40 HG 830 60 ML DALI WH IP54

The ceiling recessed luminaire DOWNLIGHT P 230 40 HG 830 60 ML DALI WH IP54 is designed for indoor use where efficient and glare-free lighting is required. It features a round shape with a diameter of 23 cm and a mounting depth of 9.5 cm. The housing is made of aluminium, ensuring a robust and durable construction. The luminaire is equipped with DALI 2 dimming, allowing flexible light control. With an IP54 rating, it is protected against dust and splashing water, while the IK08 impact resistance class provides high durability against mechanical impacts. The luminaire has a declared lifetime of 50,000 hours and offers a light output ranging from 720 to 4,810 lumens.



Light source

2545259	A to G: B

Item no.	1011301
IP Code	IP20/IP54
Impact resistance class	IK08
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500-650mA
Safety class	II
Wattage	20 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	60.0
Level of inrush current	21 A
Duration of inrush current	180 µs
Beam angle	60°
Color	white
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Depth	9.5
Diameter	23 cm
Net weight	1.14 kg
Gross weight	1.31 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	20 cm