


DOWNLIGHT P | 230 40 HG 830 60 ML WH IP54

DOWNLIGHT P, 230 40 HG 830 60 ML WH IP54

The recessed ceiling luminaire DOWNLIGHT P 230 40 HG 830 60 ML WH IP54 is designed for installation in ceilings and is suitable for a wide range of indoor applications. It features a round cut-out shape with a diameter of 23 centimetres and an installation depth of 9.5 centimetres. The housing is made of aluminium and offers a protection rating of IP54, providing protection against dust and splashing water. The luminaire achieves an impact resistance class of IK08, offering enhanced protection against mechanical impacts. With a luminous flux ranging from 2130 to 4670 lumens and a service life of 50,000 hours, it is suitable for continuous use.



Light source

2545259	A G B

Item no.	1011303
IP Code	IP20/IP54
Impact resistance class	IK08
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500-650mA
Safety class	II
Wattage	20 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	60.0
Level of inrush current	21 A
Duration of inrush current	180 µs
Beam angle	60°
Color	white
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Depth	9.5
Diameter	23 cm
Net weight	1.14 kg
Gross weight	1.31 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	20 cm