


TRACK PANEL 3PH. 120 830/840 | WB ML BK DALI

TRACK PANEL, 3PH. 120 830/840 WB ML BK DALI

The TRACK PANEL is a wide-area LED solution for 3-phase tracks and is ideal for uniform, low-glare general lighting in retail, office and commercial areas. With multi-lumen and multi-colour function and optional DALI control, it enables flexible adaptation to project-specific requirements.



Item no.	1011399
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200/250/300/350mA
Safety class	I
Wattage	39 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	22.18 A
Duration of inrush current	262 µs
Beam angle	90°
Color	black
CRI	80
Binning	3.0000
LXXBXX data	L80B10
Service life	100 000 h
Length	57.8 cm
Width	18.9 cm
Height	10.5 cm
Net weight	2.93 kg
Gross weight	3.4 kg