


TUBULAR P 1200 560 850 | WH DALI2 OPL PMMA

TUBULAR P, 1200 560 850 WH DALI2 OPL PMMA

The TUBULAR P damp-proof luminaire is designed for use in demanding environments with high moisture exposure. It features a luminous flux of 6000 lumens and a service life of up to 100,000 hours. The housing is made of plastic and equipped with a PMMA optic, which ensures uniform light distribution. The luminaire is 145 cm long and has a diameter of 7.5 cm. It is equipped with DALI 2 dimming technology, allowing flexible control. The protection rating of IP66/IP69K guarantees protection against dust ingress and powerful water jets, while the IK07 impact resistance class ensures robustness against mechanical impacts.



Item no.	1011476
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	35 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	19 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.51 kg
Gross weight	1.55 kg