


TUBULAR P 1500 800 840 | WH DALI2 OPL PMMA

TUBULAR P, 1500 800 840 WH DALI2 OPL PMMA

The TUBULAR P damp-proof luminaire is designed for use in demanding environments with high moisture levels. It has a length of 145 cm and a diameter of 7.5 cm. With a luminous flux of 8,400 lumens, it provides bright and uniform illumination. The luminaire is equipped with a PMMA opal diffuser that distributes the light glare-free. Dimming is carried out via DALI 2 technology, allowing flexible control. The housing is robustly constructed and protects the luminaire according to protection class IP66/IP69K against ingress of dust and water. The impact resistance corresponds to IK07 class, making the luminaire resistant to mechanical stress. The declared service life is 100,000 hours.



Item no.	1011478
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	50 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	19 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.76 kg
Gross weight	1.8 kg