


TUBULAR P 1500 930 850 | WH DALI2 CLR PMMA

TUBULAR P, 1500 930 850 WH DALI2 CLR PMMA

The TUBULAR P wet room luminaire is designed for use in areas with high humidity and demanding environmental conditions. It offers a luminous flux of 9,700 lumens and a long service life of 100,000 hours. The housing is made of plastic and features a PMMA optic that ensures uniform light distribution. The luminaire is 145 cm long with a diameter of 7.5 cm. It is equipped with DALI 2 dimming technology, allowing flexible control. The IP66/IP69K protection rating and IK07 impact resistance class guarantee high durability against dust, water, and mechanical impacts.



Item no.	1011522
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	58 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	30.0
Number of luminaires at LS C16A	49.0
Level of inrush current	17 A
Duration of inrush current	30 µs
Beam angle	90°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.96 kg
Gross weight	2 kg