


TUBULAR P 1200 500 850 | WH DALI2 OPL PC

TUBULAR P, 1200 500 850 WH DALI2 OPL PC

The TUBULAR P is a damp-proof luminaire designed for use in demanding environments requiring high protection ratings. It features a robust polycarbonate cover and offers an ingress protection rating of IP66/IP69K as well as impact resistance class IK10. With a length of 115 cm and a diameter of 7.5 cm, it is intended for installation in areas exposed to moisture and dust. The luminaire delivers a luminous flux of 5300 lumens and is equipped with DALI 2 dimming technology, allowing flexible control of light intensity. The TUBULAR P is engineered for professional applications in industry, commercial, and public buildings where a reliable and durable lighting solution is required.



Item no.	1011525
IP Code	IP66/IP69K
Impact resistance class	IK10
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	35 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	30.0
Number of luminaires at LS C16A	49.0
Level of inrush current	17 A
Duration of inrush current	222 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	115 cm
Diameter	7.5 cm
Net weight	1.51 kg
Gross weight	1.55 kg