


TUBULAR P 1500 680 830 | WH DALI2 OPL PC

TUBULAR P, 1500 680 830 WH DALI2 OPL PC

The TUBULAR P wet room luminaire is designed for use in demanding environments with high humidity and dust. It delivers a luminous flux of 7,500 lumens and a declared lifetime of 100,000 hours. The housing is made of polycarbonate and measures 145 cm in length with a diameter of 7.5 cm. The luminaire is equipped with a DALI 2 dimming function, allowing flexible control. Protection rating IP66/IP69K ensures high protection against water and dust ingress, while the IK10 impact resistance class guarantees mechanical durability. The TUBULAR P is therefore suitable for professional use in wet rooms, industrial facilities, and similar areas where robust and long-lasting lighting solutions are required.



Item no.	1011526
IP Code	IP66/IP69K
Impact resistance class	IK10
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	50 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	284 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.76 kg
Gross weight	1.8 kg