
EASYLIGHT SPOT 500 440 930 | WB WH ML

EASYLIGHT SPOT, 500 440 930 WB WH ML

Whether for industrial buildings, supermarkets or logistics centres, the EASYLIGHT LED trunking system combines maximum flexibility, outstanding efficiency and high-output lighting technology in a modular system. The EASYLIGHT SPOT enables targeted accent lighting within the system. Offering a CRI >90, multiple colour temperatures and optional reflectors for different beam angles, it delivers precise light control. Available in black or white and optionally with DALI.



Item no.	1011531
IP Code	IP20
Impact resistance class	IK02
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300-750
Safety class	I
Wattage	12 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	62.0
Number of luminaires at LS C16A	62.0
Level of inrush current	1.85 A
Duration of inrush current	74 µs
Beam angle	36°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	50 cm
Width	7.9 cm
Height	1.8 cm
Diameter	9 cm
Net weight	1.66 kg
Gross weight	1.78 kg