


TRACK LINE S 3PH. 39 830/835/840 DWB ML | BK

TRACK LINE S, 3~ Spot, 39 830/835/840 DWB ML BK

The TRACK LINE S 3~ spot is a three-phase spotlight designed for indoor use. Typical application areas include commercial and public spaces where targeted lighting is required. The luminaire offers a light output ranging from 2200 to 4000 lumens and a declared service life of 100,000 hours. The housing is made of aluminium combined with PMMA optics and measures 57.8 cm in length, 6.47 cm in width, and 7 cm in height. Protection class IP20 and impact resistance rating IK02 ensure safe operation under typical indoor conditions. Installation is as a track system spotlight, providing flexible adjustment options.



Item no.	1011582
IP Code	IP20
Impact resistance class	IK02
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	14 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	31.0
Number of luminaires at LS C16A	51.0
Level of inrush current	12.62 A
Duration of inrush current	276 µs
Beam angle	120°
Color	black
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	57.8 cm
Width	6.5 cm
Height	7 cm
Net weight	0.71 kg
Gross weight	0.81 kg