


# TRACK LINE M 3PH. 84 830/835/840 DWB ML | WH

**TRACK LINE M, 3~ Spot, 84 830/835/840 DWB ML WH**

The TRACK LINE M 3~ spot is a three-phase spotlight luminaire particularly suitable for indoor use, for example in showrooms, retail spaces, or office environments. The luminaire offers a light output ranging from 4400 to 8300 lumens and is available with a colour temperature of 3000 K, 3500 K, or 4000 K, allowing flexible adaptation to different lighting requirements. The housing is made of aluminium combined with an optic made of PMMA and measures 115.2 cm in length, 6.47 cm in width, and 7 cm in height. The IP20 protection rating and IK02 impact resistance ensure reliable operation in protected indoor areas. The luminaire is designed for installation in three-phase track systems, enabling easy mounting and flexible positioning. The declared service life is 100,000 hours.




| | |
|---|---|
| Item no. | 1011588 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Primary nominal voltage | 220-240V ~ 50/60Hz |
| Secondary power / voltage | 200-350mA |
| Safety class | I |
| Wattage | 26 W |
| Ambient temperature | 80 |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 40°C |
| Number of luminaires at LS B16A | 31.0 |
| Number of luminaires at LS C16A | 51.0 |
| Level of inrush current | 12.62 A |
| Duration of inrush current | 276 µs |
| Beam angle | 120° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L80B10 |
| Service life | 100 000 h |
| Length | 115.2 cm |
| Width | 6.5 cm |
| Height | 7 cm |
| Net weight | 1.11 kg |
| Gross weight | 1.21 kg |