


TRACK LINE M 3PH. 84 830/835/840 DWB ML | WH DALI

TRACK LINE M, 3~ Spot, 84 830/835/840 DWB ML WH DALI

The TRACK LINE M 3~ spot is a three-phase spotlight designed primarily for indoor use. Typical applications include commercial and public spaces where flexible and targeted lighting is required. The luminaire offers a luminous flux range from 4400 to 8000 lumens and is equipped with a DALI 2 dimming function, allowing precise control of light intensity. The housing is made of aluminium, complemented by optical elements made of PMMA. With a length of 115.2 cm, a width of 6.47 cm, and a height of 7 cm, the luminaire is slim and unobtrusive in design. The IP20 protection rating and IK02 impact resistance ensure basic protection against contact and shocks. The luminaire is designed for track system operation, making it suitable for flexible installations in various room concepts.



Item no.	1011589
IP Code	IP20
Impact resistance class	IK02
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	27 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	32.0
Level of inrush current	16.63 A
Duration of inrush current	330 µs
Beam angle	120°
Color	white
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	115.2 cm
Width	6.5 cm
Height	7 cm
Net weight	1.11 kg
Gross weight	1.21 kg