


TRACK LINE M 3PH. 80 830/835/840 DWB ML | BK

TRACK LINE M, 3~ Spot, 80 830/835/840 DWB ML BK

The TRACK LINE M 3~ spot is a three-phase spotlight designed for indoor use, particularly in commercial or public areas. With a length of 115.2 cm and a width of 6.47 cm, the luminaire housing made of aluminium and PMMA offers a robust construction. The luminaire features a luminous flux ranging from 4300 to 8000 lumens and is designed for a service life of up to 100,000 hours. The IP20 protection rating and IK class 02 impact resistance ensure reliable operation in protected environments. Installation is carried out as a suspension on a three-phase track system, allowing flexible positioning and alignment of the light source.



Item no.	1011590
IP Code	IP20
Impact resistance class	IK02
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	26 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	31.0
Number of luminaires at LS C16A	51.0
Level of inrush current	12.62 A
Duration of inrush current	276 µs
Beam angle	120°
Color	black
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	115.2 cm
Width	6.5 cm
Height	7 cm
Net weight	1.11 kg
Gross weight	1.21 kg