


# TRACK LINE M 3PH. 80 830/835/840 DWB ML | BK DALI

**TRACK LINE M, 3~ Spot, 80 830/835/840 DWB ML BK DALI**

The TRACK LINE M 3~ Spot is a three-phase spotlight suitable for indoor use. Typical applications include commercial and public spaces where flexible and directed lighting is required. The luminaire offers a light output ranging from 4,300 to 8,000 lumens and features a DALI-2 dimming function that allows for stepless control of light intensity. The housing is made of aluminium, complemented by optical elements made of PMMA, and measures 115.2 cm in length, 6.47 cm in width, and 7 cm in height. The IP20 protection rating indicates protection against solid foreign objects larger than 12.5 mm, while the impact resistance corresponds to IK02 class. The combination of robust materials and modern control technology makes the spotlight suitable for a wide range of lighting requirements.




| | |
|---|---|
| Item no. | 1011591 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~ 50/60Hz |
| Secondary power / voltage | 200-350mA |
| Safety class | I |
| Wattage | 27 W |
| Ambient temperature | 80 |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 40°C |
| Number of luminaires at LS B16A | 19.0 |
| Number of luminaires at LS C16A | 32.0 |
| Level of inrush current | 16.63 A |
| Duration of inrush current | 330 µs |
| Beam angle | 120° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L80B10 |
| Service life | 100 000 h |
| Length | 115.2 cm |
| Width | 6.5 cm |
| Height | 7 cm |
| Net weight | 1.11 kg |
| Gross weight | 1.21 kg |