
MEDO 2 SLIM 40 | CL, PHASE

MEDO 2 SLIM 40, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 15.5 W, 85°, white

The MEDO 2 SLIM 40 is a ceiling surface-mounted luminaire suitable for indoor use. It offers a luminous flux of 1900 lumens with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 85 degrees. The luminaire is equipped with PHASE-cut dimming, allowing flexible light control. The housing is made of aluminium and steel, with a diameter of 38 centimetres and a height of 4.9 centimetres. The IP20 protection rating and IK03 impact resistance ensure a robust design for the intended application.



Item no.	1011696
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	40
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	16 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	85°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.9 cm
Diameter	38 cm
Net weight	3.3 kg
Gross weight	4.2 kg
BIG WHITE Page	199

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white