

MEDO 2 SLIM 60 | CL, PHASE

MEDO 2 SLIM 60, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 35 W, 85°, black

The MEDO 2 SLIM 60 is a ceiling surface-mounted luminaire suitable for indoor use. It features phase-cut dimming and provides a luminous flux of 4200 lumens with a colour temperature of 3000 or 4000 Kelvin. The beam angle is 85 degrees, ensuring even illumination. The housing is made of aluminium and steel, with a diameter of 58.7 cm and a height of 4.8 cm. The luminaire is rated IP20 for ingress protection and IK03 for impact resistance, making it suitable for typical indoor applications.



Item no.	1011697
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	30
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	35 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	72.0
Number of luminaires at LS C16A	72.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	85°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.8 cm
Diameter	58.7 cm
Net weight	5.8 kg
Gross weight	7.5 kg
BIG WHITE Page	199

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white