


MEDO 2 SLIM 80 | CL, PHASE

MEDO 2 SLIM 40, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 45 W, 85°, black

The MEDO 2 SLIM 80 is a surface-mounted ceiling luminaire suitable for indoor use. It has a power rating of 45 watts and offers a light colour of 3000 or 4000 Kelvin with a beam angle of 85 degrees. The luminaire features phase-cut dimming, allowing for stepless light adjustment. The housing is made of aluminium and steel, with a diameter of 76.8 cm and a height of 4.8 cm. It has an IP20 protection rating and an impact resistance class of IK03. This technical specification makes the MEDO 2 SLIM 80 a robust and versatile solution for general room lighting.



Item no.	1011699
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	20
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	1200 mA
Safety class	I
Wattage	45 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	50.0
Number of luminaires at LS C16A	50.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	85°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.8 cm
Diameter	76.8 cm
Net weight	9.5 kg
Gross weight	11 kg
BIG WHITE Page	199

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white