


STREET A MICRO 52 730 | LENS710

STREET A, MICRO 52 730 LENS710

The STREET A MICRO streetlight is a luminaire head designed for outdoor use. It is particularly suitable for illuminating streets and public pathways. The luminaire offers a light output of 5250 lumens and a declared service life of 100,000 hours. The housing is made of aluminium, while the cover is made of glass. With a length of 57.3 cm, a width of 22 cm, and a height of 13.1 cm, the luminaire is compactly designed. The IP66 protection rating ensures a high level of protection against the ingress of dust and water, and the impact resistance corresponds to IK09 class, providing high robustness against mechanical impacts.



Item no.	1011731
Number of different light outlets	1
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	35 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	24.88 A
Duration of inrush current	236 µs
Beam angle	160°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	57.3 cm
Width	22 cm
Height	13.1 cm
Net weight	3.6 kg
Gross weight	4.6 kg