


STREET A MIDI 180 740 | LENS710

STREET A, MIDI 180 740 LENS710

The STREET A MIDI 180 740 streetlight with LENS710 lens is designed for outdoor use and is particularly suitable for illuminating roads and public traffic areas. The luminaire head delivers a light output of 18,000 lumens and has a declared service life of 100,000 hours. The housing is made of aluminium and glass, ensuring a robust construction. With dimensions of 74 cm in length, 28.5 cm in width, and 13.2 cm in height, the luminaire is compactly designed. The IP66 protection rating provides high protection against dust and water ingress, while the IK09 impact resistance class guarantees high durability against mechanical impacts.



Item no.	1011737
Number of different light outlets	1
Tilt range	35°
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	820 mA
Safety class	I
Safety class	I
Safety class	I
Safety class	I
Wattage	120 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	5.0
Number of luminaires at LS C16A	8.0
Level of inrush current	65 A
Duration of inrush current	268 µs
Beam angle	160°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	74 cm
Width	28.5 cm
Height	13.2 cm
Net weight	6 kg