


# STREET A MICRO 52 730 | LENS906

**STREET A, MICRO 52 730 LENS906**

Luminaire head STREET A MICRO 52 730 LENS906, suitable for street lighting. The product is designed for outdoor use and offers a luminous flux of 5250 lumens. The housing is made of aluminium, with a glass cover. With dimensions of 57.3 cm length, 22 cm width, and 13.1 cm height, the luminaire is compactly designed. It features an IP66 rating, providing high protection against dust and water ingress, as well as an impact resistance class of IK09. The declared lifespan is 100,000 hours.




| | |
|---|---|
| Item no. | 1011739 |
| Number of different light outlets | 1 |
| IP Code | IP66 |
| Impact resistance class | IK09 |
| Impact resistance | 10 Joule |
| Primary nominal voltage | 220-240V V ~ 50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 35 W |
| Minimum ambient temperature | -40°C |
| Maximum ambient temperature | 50°C |
| Number of luminaires at LS B16A | 20.0 |
| Number of luminaires at LS C16A | 33.0 |
| Level of inrush current | 24.88 A |
| Duration of inrush current | 236 µs |
| Beam angle | 145° |
| Color | gray |
| CRI | 70 |
| LXXBXX data | L80B50 |
| Service life | 100 000 h |
| Risk Group | 1 |
| Length | 57.3 cm |
| Width | 22 cm |
| Height | 13.1 cm |
| Net weight | 3.6 kg |
| Gross weight | 4.6 kg |