


STREET A MICRO 52 740 | LENS906

STREET A, MICRO 52 740 LENS906

The STREET A MICRO 52 740 LENS906 is a luminaire head specifically designed for use in street lighting. The product is suitable for installation on poles and offers a powerful lighting solution with a luminous flux of 5250 lumens. The housing is made of aluminium and features a glass cover, ensuring a robust and durable construction. The dimensions are 57.3 cm in length, 22 cm in width, and 13.1 cm in height. The luminaire is protected to IP66 against the ingress of dust and water and has a high impact resistance of IK09. The declared service life is 100,000 hours, allowing for long-term operation.



Item no.	1011743
Number of different light outlets	1
Tilt range	35°
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Safety class	I
Safety class	I
Safety class	I
Wattage	35 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	24.88 A
Duration of inrush current	236 µs
Beam angle	145°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	57.3 cm
Width	22 cm
Height	13.1 cm
Net weight	3.6 kg