


STREET A MINI 135 740 | LENS906

STREET A, MINI 135 740 LENS906

The STREET A MINI 135 740 LENS906 is a luminaire head specifically designed for use in street lighting. This luminaire is suitable for outdoor installation, providing powerful and reliable illumination. With a luminous flux of 13,500 lumens, it offers high brightness for effective lighting of traffic areas. The housing is made of aluminium and features a glass cover that optimally distributes the light. The luminaire measures 66.4 cm in length, 25.1 cm in width, and 13.2 cm in height. It is protected to IP66 against dust and water ingress and has an impact resistance rating of IK09, making it robust against mechanical impacts. The declared service life is 100,000 hours.



Item no.	1011744
Number of different light outlets	1
Tilt range	35°
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	610 mA
Safety class	I
Safety class	I
Safety class	I
Safety class	I
Wattage	90 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	10.0
Number of luminaires at LS C16A	17.0
Level of inrush current	41.6 A
Duration of inrush current	238 µs
Beam angle	145°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	66.4 cm
Width	25.1 cm
Height	13.2 cm
Net weight	5.8 kg