GLENOS® 2.0 | CL, 1.2M, DALI, UGR22

GLENOS® 2.0, CL, 1.2M, DALI, UGR22, Surface-mounted ceiling luminaire, 4000 K, 17 W, white

The GLENOS® surface-mounted ceiling light 2.0 is designed for indoor use and is particularly suitable for offices, schools, and other work environments where glare-free and efficient lighting is required. With a luminous flux of 2400 lumens, it provides bright and even illumination. The housing is made of aluminium and measures 120 cm in length, 4.8 cm in width, and 7 cm in height. The luminaire features DALI and touch dimming functions, allowing flexible control of light intensity. With an IP20 protection rating, it is suitable for dust-protected indoor areas. The luminaire boasts a long service life of up to 100,000 hours and meets the requirements for low-glare workplace lighting with a UGR value of 22.



Item no.	1012164
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	25
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	450 mA
Safety class	I
Wattage	17 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	white
CRI	80
UGR ≤	22
LXXBXX data	L80B20
Service life	100 000 h
Length	120 cm
Width	4.8 cm
Height	7 cm
Net weight	3.8 kg
Gross weight	5.2 kg
BIG WHITE Page	167