


GLENOS® 2.0 | CL, 1.2M, DALI, UGR22

GLENOS® 2.0, CL, 1.2M, DALI, UGR22, Surface-mounted ceiling luminaire, 4000 K, 17 W, black

The GLENOS® 2.0 surface-mounted ceiling luminaire is designed for indoor use and is particularly suitable for offices, administrative buildings, and other commercial environments. It delivers a luminous flux of 2100 lumens and features dimmable control via DALI as well as touch technology, allowing flexible lighting adjustments. The housing is made of aluminium and measures 120 cm in length, 4.8 cm in width, and 7 cm in height. The luminaire has a glare rating of UGR22, ensuring comfortable light distribution. With an IP20 protection rating, it is suitable for dust-free indoor areas. The declared lifetime of 100,000 hours ensures long operational durability.



Item no.	1012165
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	25
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	450 mA
Safety class	I
Wattage	17 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	black
CRI	80
UGR ≤	22
LXXBXX data	L80B20
Service life	100 000 h
Length	120 cm
Width	4.8 cm
Height	7 cm
Net weight	3.8 kg
Gross weight	5.2 kg
BIG WHITE Page	167