


GLENOS® 2.0 | WL, 1.5M, DALI, UGR22

GLENOS® 2.0, WL, Surface-mounted wall luminaire, 3000 K, 20 W, 80°, black

The GLENOS® 2.0 wall-mounted luminaire is designed for indoor use and delivers a light output of 2650 lumens. It features DALI and touch dimming functions, allowing flexible light control. The housing is made of aluminium and measures 150 cm in length, 7 cm in height, and 4.8 cm in depth. With a UGR value of 22, the luminaire ensures glare-free lighting. Its IP20 rating makes it suitable for dry environments. The luminaire boasts a long lifespan of 100,000 hours, making it ideal for professional use in office, residential, or exhibition areas.



Item no.	1012167
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	40
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	550 mA
Safety class	I
Wattage	20 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	black
CRI	80
UGR ≤	22
LXXBXX data	L80B20
Service life	100 000 h
Length	150 cm
Height	7 cm
Depth	4.8
Net weight	4.3 kg
Gross weight	5.8 kg
BIG WHITE Page	320