


GRIP! S MINI | 48V, DALI, SHORT, STANDARD TRACK, Ø 3.0CM

GRIP! S MINI, 48V spot, DALI, SHORT, Standard Track, 3000 K, 4.2 W, 29°, black / gold-colored

The GRIP! S MINI is a 48V spot designed for mounting on ceiling and wall track systems. Typical applications include indoor spaces where directional lighting with a beam angle of 29° is required. The luminaire features a light colour of 3000 K and a power consumption of 4.2 W, delivering a luminous flux of 270 lumens. Control is via DALI 2, allowing for flexible dimming. The housing is made of aluminium and measures 17 cm in length, 3 cm in width, and 4 cm in height. The protection rating is IP20, and the luminaire has an impact resistance classification of IK02. The declared service life is 50,000 hours.



Light source

2093886	A D

Item no.	1012173
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Track
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	48V DC
Secondary power / voltage	100 mA
Safety class	III
Wattage	4 W
Minimum ambient temperature	0°C
Maximum ambient temperature	30°C
Beam angle	29°
Color	black/gold
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	17 cm
Width	3 cm
Height	4 cm
Net weight	0.09 kg
Gross weight	0.14 kg
BIG WHITE Page	463

Accessories

1011829	GRIP! S, decorative ring, white
1011830	GRIP! S, decorative ring, black
1011831	GRIP! S, decorative ring, nickel
1011832	GRIP! S, decorative ring, gold
1011837	GRIP! S, HONEYCOMB