
SENSER 2.0 30 | RL, SQUARE, DALI

SENSER 2.0 30, RL, square, DALI, recessed ceiling luminaire, 3000 K / 4000 K, 24 W, 90°, white

The SENSER 2.0 30 is a square recessed ceiling luminaire suitable for indoor use. It features a colour temperature of 3000 K or 4000 K and a power consumption of 24 watts with a beam angle of 90°. The housing is made of aluminium, complemented by a polycarbonate cover. The luminaire is equipped with DALI-2 dimming, allowing for flexible light control. With an IP20 protection rating and an impact resistance of IK02, it is designed for standard applications in protected indoor areas. The compact design, measuring 30 x 30 cm with a recessed depth of 2.4 cm, facilitates integration into ceilings. The declared service life is 50,000 hours.



Item no.	1012212
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	45
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	24 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	62.0
Number of luminaires at LS C16A	62.0
Level of inrush current	2.02 A
Duration of inrush current	70 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	30 cm
Width	30 cm