

LEDSTRIP SMD IP67 | S

LED STRIP SMD IP67, S, 3000 K, L: 500 cm, IP67, 5000 lm

The LED strip is suitable for use in various indoor and outdoor areas that require a slim, flexible lighting solution. With a length of 500 cm and a width of 1 cm, it provides uniform light distribution at a colour temperature of 3000 K. The housing is rated IP67, protecting the LED strip against the ingress of dust and water, making it suitable for demanding environments. The luminaire produces a light output of 5000 lumens and has a declared service life of 50,000 hours. The flat design with a height of 0.45 cm allows for discreet installation on various surfaces.

Accessories

1012303	LED STRIP CONNECTOR IP SEALING SET, 8MM, clear

Item no.	1012280
Number of different light outlets	1
IP Code	IP67
Assembly	Surface
Assembly details	Ceiling,Wall,
LED distance	0,63 cm
Safety class	III
Safety class	III
Ambient temperature	55
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	120°
CRI	90
Binning	5.0000
LXXBXX data	L80B20
Service life	50 000 h
Length	500 cm
Width	1 cm
Height	0.5 cm
Net weight	0.26 kg
Gross weight	0.37 kg
BIG WHITE Page	621