

FRAME BASIC

recessed fitting, LED, 3000K, square, silver-grey, incl. leaf springs

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a high-quality diode and available in either pure white or warm white light colour. To operate, the FRAME BASIC needs a suitable constant current driver rated at 350mA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	111262
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling,Wall
Secondary power / voltage	350 mA
Safety class	III
Wattage	1 W
Lumen	40 lm
Colour temperature	3000 Kelvin
Color	grey
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Light distribution	rotational symmetric
Light outlet	direct
Width	9 cm
Height	9 cm
Depth	6 cm
Net weight	0.224 kg
Gross weight	0.284 kg
Shape of cut-out	square
Installation length	7.5 cm

954799	

Accessories

111861	CABLE EXTENSION , for items with a 350mA plug, 1 m
112781	MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
111850	MULTIWAY CONNEC-TOR , 3 outputs with two bridges, black, max. 350-mA
112780	FLUSH-MOUNTED , FRAME, for FRAME BA-SIC, FLAT FRAME BASI-C, FLAT FRAME CURVE and FRAME CURVE
1007270	LED driver 3W , 350mA including AMP socket

Installation width	7.5 cm
Installation depth	6.6 cm
BIG WHITE Page	238