




VERLUX

recessed fitting, LED, 3000K, matt white, L/B/T 8.5/8.5/4.5 cm, 10W

The light, square recessed VERLUX fitting with a round cut-out is available in various wattages and sizes. The square recessed ceiling light is made of aluminium and comes in a white colour. The rigid Premium LED insert produces homogeneous base lighting thanks to its wide beam angle of 80°. The luminaire comes with a dimmable constant current driver and is ready for connection to the 230 V mains supply.



TECHNICAL DATA

Item no.	112682
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	11 W
Level of inrush current	13 A
Duration of inrush current	28 µs
Stroboscopic effect (SVM)	0.03
Lumen	940 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	white
CRI	80
LXXBXX data	L70B50

916585	

Service life	35000 h
Length	8.5 cm
Width	8.5 cm
Depth	4.5 cm
Net weight	0.171 kg
Gross weight	0.238 kg
Shape of cut-out	round
Installation depth	4.5 cm
Installation diameter	7.5 cm
BIG WHITE Page	227