




VERLUX

recessed fitting, LED, 3000K, matt white, L/B/T 13.5/13.5/7.5 cm, 20W

The light, square recessed VERLUX fitting with a round cut-out is available in various wattages and sizes. The square recessed ceiling light is made of aluminium and comes in a white colour. The rigid Premium LED insert produces homogeneous base lighting thanks to its wide beam angle of 80°. The luminaire comes with a dimmable constant current driver and is ready for connection to the 230 V mains supply.



TECHNICAL DATA

Item no.	112692
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	22 W
Rated standby power	0.5 W
Stroboscopic effect (SVM)	0.06
Lumen	1800 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	35000 h

916379	

Light distribution	rotational symmetric
Light outlet	direct
Length	13.5 cm
Width	13.5 cm
Depth	7.5 cm
Net weight	0.353 kg
Gross weight	0.491 kg
Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	12.5 cm
BIG WHITE Page	227