




KADUX | EL, triple, PHASE

KADUX 3 SET, recessed fitting, triple-headed LED, 3000 K, rectangular, matt white, 38°, 3x9 W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 3 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



Light source

916451	A G E

Item no.	115721
Rotating or tilting	tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	false
Dimming technology	Leading edgetrailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350mA
Safety class	II
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Level of inrush current	4 A
Duration of inrush current	110 µs
Stroboscopic effect (SVM)	0.0100
Beam angle	38°
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40 000 h
Length	21 cm
Width	9 cm
Height	8.5 cm
Net weight	0.77 kg
Gross weight	0.85 kg
Shape of cut-out	square
Installation length	20 cm
Installation width	8 cm