

KADUX 1 SET

recessed fitting, single-headed LED, 3000K ex, square, matt black, 30°, 29W, incl. driver, clip springs

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This XL Type LED Set is multi-directional, allowing individual focus of the light beam. Its high output, warm white Premium COB LED produces exceptionally powerful illumination. The KADUX 1 SET recessed fitting comes ready for direct connection to 230V mains.



TECHNICAL DATA

Item no.	115730
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	29 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.33 W
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	2700 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	30000 h

916475	

Length	19.5 cm
Width	19.5 cm
Height	12.5 cm
Net weight	1.575 kg
Gross weight	1.952 kg
Shape of cut-out	square
Installation length	17 cm
Installation width	17 cm
Installation depth	12.5 cm