




# KALU TRACK

**spot for 240V 1-phase track, LED, 3000K, white, incl. 1-phase adapter**

Adjustable KALU TRACK spotlight with suitable adapter for the 1-circuit 240V track system. Designed as an extension of the popular KALU series, this new track-mounted spotlight takes on the shape of the product family. The incorporated LED module guarantees high light output with low electricity consumption. To meet all lighting requirements, versions with G53 and GX53 sockets for the 1- and 3-circuit systems are also available. This luminaire contains built-in LED lamps.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 143731 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary Bar and tiltable |
| **IP Code** | IP 20 |
| **Assembly** | Surface |
| **Assembly details** | Ceiling,Track Ceiling,Track Wall,Wall |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Safety class** | II |
| **Wattage** | 13 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Level of inrush current** | 3 A |
| **Duration of inrush current** | 10 µs |
| **Lumen** | 970 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 95 ° |
| **Color** | white |
| **CRI** | 80 |
| **LXXBXX data** | L70B50 |
| **Service life** | 25000 h |

| | |
|---|---|
| 703130 |  |

| | |
|---|---|
| **Length** | 12 cm |
| **Height** | 15 cm |
| **Diameter** | 10.5 cm |
| **Net weight** | 0.45 kg |
| **Gross weight** | 0.542 kg |
| **BIG WHITE Page** | 520 |