


# BIMA 1

**spot for 240V 3-phase track, single-headed, QPAR51,-round, silver-grey max. 50W, incl. 3-phase adapter**

Adjustable high-voltage spot BIMA 1 with suitable adapter for the 240V 3-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 152242 |
| **Socket** | GU10 |
| **Number of sockets** | 1 |
| **Tilt range** | 200 ° |
| **Horizontal rotation range** | 350 ° |
| **Rotating or tilting** | rotary Bar and tiltable |
| **IP Code** | IP 20 |
| **Assembly** | Surface |
| **Assembly details** | Ceiling,Track Ceiling |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Safety class** | II |
| **Wattage** | 50 W |
| **Color** | grey |
| **Light outlet** | direct |
| **Length** | 8 cm |
| **Height** | 15 cm |
| **Diameter** | 6 cm |
| **Net weight** | 0.293 kg |
| **Gross weight** | 0.358 kg |
| **BIG WHITE Page** | 541 |

## Recommended lamp

| | |
|---|---|
| 1005075 | LED lightbulb QPAR51 , GU10, 2700K, grey |
| 1005081 | LED lightbulb QPAR51 , GU10, 4000K, grey |
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |
| 1005078 | LED lightbulb QPAR51 , GU10, 3000K, grey |