




KARPO

recessed fitting, single-headed, LED, 3000K, white, flat canopy, 7.5W

KARPO series lights are available in white and black. It has a spot in a cylindrical shape which can be individually aligned via the hinge on the flat canopy. The swivel and tilting range allows you to optimally light up the room. The integrated premium LEDs provide high energy efficiency. In addition, the luminaire has a high colour rendering index of over 90. To operate, the single-headed FRAME Spots needs a suitable constant current driver rated at 500mA.



TECHNICAL DATA

Item no.	152381
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling,Wall
Secondary power / voltage	500 mA
Safety class	III
Wattage	7.5 W
Maximum ambient temperature	40 °C
Lumen	470 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Light distribution	rotational symmetric
Light outlet	direct
Length	15.2 cm
Height	5.5 cm
Diameter	3 cm
Net weight	0.177 kg

916381	

Accessories

1007226	LED driver 21W 500mA
1007227	LED driver 20W 350mA-/500mA PHASE
1007229	LED driver 25W 150-700-mA DALI TOUCH

Gross weight	0.281 kg
Shape of cut-out	round
Installation depth	2 cm
Installation diameter	7 cm
BIG WHITE Page	232