




ROCCI 125

outdoor inground fitting, LED, 3000K, IP67, square, stainless steel 316, max. 6W

The inground fitting ROCCI 125 has a square stainless steel shade with a transparent glass cover and is fitted with a COB LED module. With protection class IP67, the luminaire is available with two shapes of shades and is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly.



TECHNICAL DATA

Item no.	227604
IP Code	IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	5 A
Duration of inrush current	25 µs
Temperature at glass (light emission)	48 °C
Stroboscopic effect (SVM)	0.02
Lumen	580 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	stainless steel
CRI	80
LXXBXX data	L70B50

916530	

Service life	40000 h
Length	12.6 cm
Width	12.6 cm
Depth	12.7 cm
Net weight	1.019 kg
Gross weight	1.17 kg
Shape of cut-out	round
Installation depth	12.3 cm
Installation diameter	11.3 cm
BIG WHITE Page	854