





ADI

outdoor recessed wall light, LED, 3000 K, IP55, anthracite, 15,4 W

The ADI recessed wall light is made of aluminium and is fitted with powerful premium LEDs. It has an indirect, glare-free light outlet which points downwards. The curved design was developed by the designer, David Morgen. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use. The electrical connection to the luminaire can be made with 100-277V. For easy installation, we recommend the appropriate mounting pot as an accessory.



TECHNICAL DATA

Item no.	233635
IP Code	IP55
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Primary nominal voltage	100-277V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	17 A
Duration of inrush current	35 µs
Lumen	940 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
Service life	25000 h
Width	30 cm
Height	13 cm
Depth	11.1 cm
Net weight	1.608 kg
Gross weight	1.872 kg

916465	

Accessories

233639	MOUNTING POT , for ADI outdoor recessed wall light, black

Shape of cut-out	square
Installation length	10.8 cm
Installation width	25 cm
Installation depth	8.8 cm
BIG WHITE Page	950