

Solid Tyre With Rim & Holes

For each size we can produce solid tyre with rim together. Fits for many skid steer loaders. Such as: Bobcat, Caterpillar, Volvo, Komatsu, LIUGONG, Lonking, XCMG, Chenggong, Zoomlion, Doosan, etc.

1.It is the state patent product with independent innovation technology, leading the development trend of solid tires.

2.Compared with traditional solid tires, it has the advantages like fast installation,light weight, better shock absorption and heat yield, reduce the impact load to axle, increase the speed o vehicles etc.

3.Compared with traditional pneumatic tires, it has many advantages such as puncture-resistant, maintenance-free, long life, etc.

Sizes information:

Sizes information:

No.	Size of Tire	Rim Size	Outside Diamete	Section Width	Net Weight(Kg)	Max Load (Kg)
			±5mm	±5mm	±1.5%kg	Other Industrial Vehicles
1	10x16.5 (30x10-16)	FB/Hole	788	250	117	3700
2	12x16.5 (33x12-20)	FB/Hole	840	275	131	4500
3	16/70-20	FB/Hole	1060	400	322	8830
4	16/70-20(Economy size)	FB/Hole	940	330	230	6620
5	38.5x14-20	FB/Hole-	966	350	280	7070
6	385/65-24 (385/65-22.5)	FB/Hole	1062	356	318	7390
7	445/65-24 (445/65-22.5)	FB/Hole	1152	428	429	10040
8	17.5-25	FB/Hole -	1368	458	655	13400
9	23.5-25	FB/Hole -	1620	580	1040	23400
10	26.5-25	FB/Hole -	1736	650	1395	29810