

# SW32 WHEELED SKID STEER LOADER

The SW32 increases productivity with maximum power for every jobsite. Highlights of this machine include, Controls for every operator, filter free after-treatment, expansive maintenance access, high flow package and side counter weights.



| PERFORMANCE DATA                        |                                                         |
|-----------------------------------------|---------------------------------------------------------|
| Max. Operating Power at operating speed | 100 @21                                                 |
| Engine Type                             | Kohler KDI, Liquid Cooled, 4-cylinder, turbo diesel en- |
| Rated Operating Capacity @ 50%          | 3200 lbs                                                |
| Tipping Load                            | 6400 lbs                                                |
| Fuel Tank Capacity                      | 40 gal                                                  |
| Hydraulic Tank Capacity                 | 3.4 gal                                                 |
| Max travel speed, single/two-speed      | 7.2 / 11.9 mph                                          |
| Auxiliary relief pressure               | 3500 psi                                                |
| Auxiliary Hyd. Flow rate, low/ high     | 22.1 / 31.7 gpm                                         |
| MECHANICAL DETAILS                      |                                                         |
| Operating weight                        | 8, 629 lb                                               |
| Ground clearance                        | 9"                                                      |
| Length without Bucket                   | 145.4 "                                                 |
| Length with Bucket                      | 117.5 "                                                 |
| Overall width                           | 71.9"                                                   |
| Overall Height                          | 83.2"                                                   |
| Bucket Hinge Pin Height                 | 134.8 "                                                 |
| Breakout force—bucket                   | 2461 lbf                                                |
| Angle of departure                      | 23°                                                     |
| Reach at height max.                    | 37.4 "                                                  |
| Dump angle at height max                | 44°                                                     |
| Standard Tires                          | 12 x 16.5                                               |

## PRODUCT DETAILS

- 510 lbs Counter weights
- Offers 3,200 lbs (1,451 kg) of rated operating capacity at 50%
- 134.8" top of class hinge pin height
- Forward tipping cab with arms down
- 4 year, 4,000 hour warranty with Tier 4 Final Kohler KDI turbo diesel engine
- DOC/SCR system eliminates DPF and regeneration
- Controls for any operator including EH hand-foot and selectable EH (ISO and H-pattern)
- Optional high flow package provides up to 4,000 psi @ 37.4 gpm (switchable) to the Aux hydraulics for improved attachment performance

**PRICE NEW: \$87,500**