

*HIKVISION*

# DENSITY CONTROL CONTROL BROCHURE

---





Flexible Deployment



Real Time Alert



High Accuracy



Real Time Display


### What is Density control?

In the current climate of social distancing requirements Hikvision's density control solution allows you to monitor and control the amount of people allowed in an establishment at any given time making the internal environment more spacious and much safer for the people inside, the solution utilises existing IP based front and back end technology using a customised operating system which allows the counting information to be displayed on a friendly GUI from either the local monitor output or remotely using a PC or digital sign hardware. The technology has been implemented into several product lines allowing you to choose the most appropriate solution based on the amount of entrances/exits needing coverage from a single entrance up to a very large installation with many entrances/exits across several sites.

The Density control counting information is displayed on a friendly GUI allowing people waiting to easily see how many people are inside and also how many more can enter, the GUI also displays green (for go) with a customisable message when it is OK to enter and red (for stop) with a customisable message when the premises is full. For sites with multiple entrances using the I series NVR or Hik-Central solution it is possible to group your entrances together in to one single counting GUI which handles the traffic from all entrance/exits keeping the real time display up to date.

## Single Door Camera Standalone

- Ideal for small shops
- Fast deployment and cost effective, only one camera and one monitor required
- Basic numeric data shows number of people in premises
- Real time alert and voice prompt from camera when threshold is reached



## Single Door with I Series NVR

- Ideal for retail shops with single entrance/exit
- User friendly and informative real time data screen displays maximum number accepted and current number inside store with green or red warning signs
- Ideal for placing near entrance, so customers can identify the display
- Fast deployment, only one camera, one NVR and one monitor required




## Multi-Door I Series NVR

- Ideal for multi entrance/exit market
- NVR calculates the total figure from all the cameras and displays intuitive real time data with warning symbols



## Multi-Door HikCentral

- Ideal for large sites with multiple entrances and exits like markets places, supermarkets, depots and distributions centres across multiple locations
- HikCentral software calculates the total figures from all the cameras and displays intuitive real time data with warning symbols
- Central management to view and review whole system via HikCentral software
- Business intelligence reports for further analysis





Post Office



Supermarket



Retail

Banks



People counting Camera 1




People counting Camera 2

Network



Network




**Highlight**

- Ideal for small shop Fast deployment and cost effective, only one camera, one monitor and one digital signage box required
- Play advertising pictures or videos in a loop.


Hikvision digital sign solutions are designed to display company advertising, messages or instructions in the form of stills or moving video but using a special operating system they have now been integrated to be able to display density control and temperature screening information on the screen at the same time. The units are available as standalone digital signs or as a digital sign box (DS-D60C-B) which can convert a conventional monitor into a digital sign solution.

digital sign technology can be used to display important density control and temperature screening information alongside what could be a message or set of instructions or simply advertising a product, this flexibility makes the digital sign a powerful option when deploying density control and temperature screening solutions within a whole host of environments.






Single Entrance/Exit Deployment up to 100 people counting threshold.



Multiple Entrance/Exit Deployment, multiple people counting cameras can be used for each entrance up to the maximum camera inputs of the I series NVR.







Large Scale deployment multiple entrance/exit deployment across multiple sites.



Solution Business Flow



■ **Optional**



### Models

#### Cameras:

- DS-2CD6825G0/C-IS
- DS-2CD6825G0/C-IVS

#### K Series NVRs

- DS-7604NI-K1/4P
- DS-7608NI-K2/8P
- DS-7616NI-K2/16P

#### I Series NVRs

- DS-7608NI-I2/8P
- DS-7616NI-I2/16P
- DS-7716NI-I4
- DS-7732NI-I4
- DS-7716NI-I4/16P
- DS-7732NI-I4/24P
- DS-9664NI-I8
- DS-9632NI-I8

#### PoE Switches

- DS-3E0106HP-E
- DS-3E0310HP-E
- DS-3E0109P-E(C)
- DS-3E0318P-E
- DS-3E0326P-E

#### Monitors

- DS-D5022FN
- DS-D5024FN
- DS-D5027FN

#### Workstations:

- HC/WORKSTATION/H/GPU
- HC/WORKSTATION/M/GPU

**Contact Details**