

Cold Weld HC-36 Plug In Hook Mounts or C-Clip

Part Description	Post Ht. (+/- Tol.)	Grd. Pin	Lead Dia. & Lead Lgth. (+/- Tol.)	Mount Information					
				Center Lead Type & Ht.	Contact Area Dim.	Mount To Mount	Mount Ht.	Wdth. x Lgth. Thk. x Wdth.	Temp. & Mat'l.
CW-105-NP-A-HMBD	.070+/-0.008	No	.050 (2 Plcs.) .236+/-0.010	N/A	.015 Slot & .045 R. Ref.	.545+/-0.015	.305+/-0.015	.005 x .040	S.S. 301, Spring Hard
CW-105-NP-A-HMCE	.070+/-0.008	No	.050 (2 Plcs.) .236+/-0.011	N/A	.020 Slot & .045 R. Ref.	.545+/-0.015	.330+/-0.015	.005 x .040	S.S. 301, Spring Hard
CW-105-B-HMCD IS	.090+/-0.008	No	.050 (2 Plcs.) .236+/-0.012	N/A	.020 Slot & .045 R. Ref.	.435+/-0.015	.305+/-0.015	.005 x .040	S.S. 301, Spring Hard
CW-105-B-HMCD	.090+/-0.008	No	.050 (2 Plcs.) .236+/-0.013	N/A	.020 Slot & .045 R. Ref.	.545+/-0.015	.305+/-0.015	.005 x .040	S.S. 301, Spring Hard
CW-105-B-XP2064CB.600	.090+/-0.008	No	.050 (2 Plcs.) .236+/-0.014	N/A	.020-.034 Slot & .065 R. (Oval Slot)	.600 Ref.	.305+/-0.015	.010 x .062	S.S. Full Hard