

Resistance Weld .498 x .798 (4 Lead)
(D.I.L.) Dual In Line Or (D.I.P.) Dual Inline Package

Part Description	Header Information (Pin Grid. Pattern .300x.600)								
	Post Ht.	Posts	Lead Lgth.	Leads	Insulated Pin Position	Grd. Pin Position	S.O. Ht. +/- .005 & Grid. Pattern	S.O.	Header Mat'l.
RR-498798-BH	.050+/- .005	4	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-CT	.205+/- .005	4	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-DJ	.205+/- .005	4	.250+/- .020	4	1,7,8 & 14 Thru	N/A	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-EY	.250+/- .010	4	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-F	.050+/- .005	4	.250+/- .020	4	1,7,8 & 14 Thru	N/A	N/A	N/A	C.R.S.
RR-498798-FR	.350+/- .010	4	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-FZ	.065+/- .005	4	.250+/- .020	4	1,7 & 8 Thru	14 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-GA	.065+/- .005	4	.250+/- .020	4	1,9 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-KN	.230+/- .010	4	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	N/A	C.R.S.
RR-498798-NX	.065+/- .005	4	.250+/- .020	4	7,8 & 14 Thru	1 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-PJ	.180+/- .005	4	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-PJ-S5	.180+/- .010	4 Flattened .110+/- .005	.250+/- .020	4	1,8 & 14 Thru	7 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-U	.050+/- .005	4	.250+/- .020	4	1,7 & 8 Thru	14 Thru	.025 .180x.480 Grid.	4	C.R.S.
RR-498798-LD	.297+/- .010	7	.250+/- .020	3 4	6,9 & 13 Posts Only 1,8 & 14 Thru	7 Thru	.025 .150x.500 Grid.	4	C.R.S.
RR-498798-LD-S4	.297+/- .010	7 Flattened .227+/- .005	.250+/- .020	4	6,9 & 13 Posts Only 1,8 & 14 Thru	7 Thru	.025 .150x.500 Grid.	4	C.R.S.