

Cold Weld HC-43 Tab Mounts or Flag Clip

| Part Description | Post/Lead Dia. & Lead Lgth. | Grd. Pin | Mount Information | | | | | |
|-----------------------------------|--------------------------------|----------|------------------------|-------------------------------------|----------------|--------------|------------------|-------------------------|
| | | | Center Lead Type & Ht. | Contact Area Dim. | Mount To Mount | Mount Ht. | Thk. x Wdth. | Temp. & Mat'l. |
| CW-185-17B | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .216+/- .015 | .138+/- .015 | .003 x .020/.040 | C770 Full Hard |
| CW-185-17D | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .216+/- .015 | .178+/- .015 | .003 x .020/.040 | C770 Full Hard |
| CW-185-17B (SS) | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .216+/- .015 | .138+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |
| CW-185-17K (SS) | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .216+/- .015 | .130+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |
| CW-185-17C (SS) W/IS B.55 DEG. | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .241 Ref. | .096+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |
| CW-185-17I (SS) B.260 | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .260+/- .015 | .143+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |
| CW-185-17A B.300 | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .300+/- .015 | .185+/- .015 | .003 x .020/.040 | C770 Full Hard |
| CW-185-17A (SS) B.300 | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .300+/- .015 | .185+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |
| CW-183-CFG-A-17A (SS) B.300 | .019 (3 Plcs.) .620+/- .020 | No | Grd. .037 Seat | .035 Thk. x .045 Wd. x .035 Tall | .300+/- .015 | .185+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |
| CW-185-17A B.310 | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .310+/- .015 | .183+/- .015 | .003 x .020/.040 | C770 Full Hard |
| CW-185-17J B.310 | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .310+/- .015 | .198+/- .015 | .003 x .020/.040 | C770 Full Hard |
| CW-185-17A (SS) B.310 | .019 (2 Plcs.) .520+/- .020 | No | N/A | .035 Thk. x .045 Wd. x .035 Tall | .310+/- .015 | .183+/- .015 | .003 x .020/.040 | S.S. 301 Spring Hard |