

Resistance Weld HC-50 Welded Slot Mounts or Slot Mount

Part Description	Post/Lead Dia. & Lead Lgth.	Grd. Pin	Mount Information					
			Center Lead Type & Ht.	Contact Area Dim.	Mount To Mount	Mount Ht.	Thk. x Wdth.	Temp. & Mat'l.
RR-45-WSM019B INSIDE	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.130+/- .015	.100+/- .015	.003 x .030	C770, Full Hard
RR-45-WSM019C INSIDE	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.130+/- .015	.085+/- .015	.003 x .030	C770, Full Hard
RR-45-WSM019B	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.170+/- .015	.100+/- .015	.003 x .030	C770, Full Hard
RR-45-WSM019C	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.170+/- .015	.085+/- .015	.003 x .030	C770, Full Hard
RR-45-WSM019F	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.170+/- .015	.128+/- .015	.003 x .030	C770, Full Hard
RR-45-CGF-D-WSM018A B.210	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush	.011 Wd. x .075 Lg.	.210+/- .015	.141+/- .015	.003 x .030	C770, Full Hard
RR-45-CGF-D-WSM019A B.210	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush	.005 Wd. x .075 Lg.	.210+/- .015	.141+/- .015	.003 x .030	C770, Full Hard
RR-45-CGF-D-WSM019F B.185	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush	.005 Wd. x .075 Lg.	.185+/- .015	.126+/- .015	.003 x .030	C770, Full Hard
RR-45-CGFTF-WSM019F B.185	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush Tack Fork .035 SH	.005 Wd. x .075 Lg.	.185+/- .015	.126+/- .015	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-TF-WSM019F B.185	.019 (2 Plcs.) .520+/- .020	Fork Only	Tack Fork Grd. .035 SH	.005 Wd. x .075 Lg.	.185+/- .015	.126+/- .015	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-WSM018A B.210	.019 (2 Plcs.) .520+/- .020	No	N/A	.011 Wd. x .075 Lg.	.210+/- .015	.141+/- .015	.003 x .030	C770, Full Hard
RR-45-WSM018C INSIDE	.019 (2 Plcs.) .520+/- .020	No	N/A	.011 Wd. x .075 Lg.	.130+/- .015	.085+/- .015	.003 x .030	C770, Full Hard
RR-45-WSM019F B.185	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.185+/- .015	.126+/- .015	.003 x .030	C770, Full Hard
RR-45-DB002A B.185	.019 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.185+/- .015	.136+/- .010	.004 x .032	C770, 1/2 Hard
RR-45-DB002A B.196	.019 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.196+/- .015	.135+/- .010	.004 x .032	C770, 1/2 Hard
RR-45-B-1231 B.196	.019 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .093 Lg.	.196+/- .010	.129+/- .010	.004 x .027	C770, 1/2 Hard
RR-45-DF	.019 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .025 Dp.	.148+/- .008	.037+/- .005	.008 x .040	52 Alloy
RR-45-CGFTF4-TF005 IS	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush Tack Fork .055 SH	.010 Wd. x .015 Dp.	Straight Up	.060+/- .005	.003 x .030	C770, Full Hard Ni. Silver 1/2 Hd.
RR-45-TF005 I/S BENT 20 DEGREES	.019 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .015 Dp.	20 Degrees Inward	.060+/- .005	.003 x .030	Ni. Silver 1/2 Hd.
RR-45-CGFTF-CM011A	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush Tack Fork .035 SH	Claw Mount .005 Wd. x .015 Lg.	.200+/- .005	.125+/- .005	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-CIF-CM011A	.019 (3 Plcs.) .520+/- .020	No	Center Insulated Fork .037 SH	Claw Mount .005 Wd. x .015 Lg.	.200+/- .005	.125+/- .005	.003 x .030	C770, Full Hard
RR-45-TF-CM011A	.019 (2 Plcs.) .520+/- .020	Fork Only	Grd. .035 SH	Claw Mount .005 Wd. x .015 Lg.	.200+/- .005	.125+/- .005	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-SCM018AA B.075	.019 (2 Plcs.) .520+/- .020	No	N/A	Slotted Claw Mount .005 Wd. x .073 Lg.	.100 Ref. Top .075 Ref. Bottom	.160 Ref. Top .087+/- .010	.003 x .030	C770, Full Hard
RR-45-015A-DB001A B.212	.015 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .104 Lg.	.212+/- .015	.131+/- .010	.004 x .032	C770, 1/2 Hard
RR-45-DB001A B.212	.019 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .104 Lg.	.212+/- .015	.131+/- .010	.004 x .032	C770, 1/2 Hard
RR-45-A-CM011A	.019 (2 Plcs.) .520+/- .020	No	N/A	Claw Mount .005 Wd. x .015 Lg.	.200+/- .005	.125+/- .005	.003 x .030	C770, Full Hard